Now at your dealer or **wh.com**



Class B, simply profitable





The essentials

of sterilization

lina

Simple and expandable.

Lina is one of the range of W&H sterilizers which offers maximum safety and an excellent price-performance ratio with its Class B cycles and a built-in USB data log.



Select cycle >B UNIVERSAL 134°C #00136

Class B cycles exclusively

The Lina sterilizer works exclusively with Class B cycles and with short ECO B cycles for smaller loads.



Simple navigation

All sterilization options are easily accessible with the easily operated keypad.



ECO B sterilization program

The cycle time can be reduced by half for small loads.



Built-in data log

The built-in data log means that sterilization cycles can be saved to a USB stick without needing cables and external boxes.



Barcode label printer

The LisaSafe label printer can be connected to the sterilizer to print barcodes. Combined with the built-in data log your traceability system is enhanced.

Your advantages at a glance

- The ECO B cycle reduces the cycle time by half
- Low-noise operation with the patented water separation system
- User-friendly keypad for simple navigation to all sterilization options
- Built-in dust filter to protect internal components
- Programmable cycle start
- > Excellent value for money
- Integrated automatic water filling valve (optional)
- Automatic digital cycle recording on USB stick (optional)

Pictures are for illustrative purposes only. Additional equipment and accessories shown are not included as standard.

20409 AEN Rev. 009 / 16.01.2020 Subject to alterations

Technical data

		B-Universal 134			B-Prion 134			B-Universal 121
Temperature		134 °C			134 °C			121 °C
Holding time		3.5'		18'			15'	
Total cycle duration including drying		ECO-B	Full Load	Typical Load	ECO-B	Full Load	Typical Load	Full Load
	Lina 17	29'	54'	49'	44'	69'	64'	75'
	Lina 22	33'	64'	55'	48'	79'	70'	79'
Max load: ECO/full/typical loads/ Max porous load		Lina 17: 0.5kg / 4kg / 2kg / 1.5kg Lina 22: 0.5kg / 5kg / 2kg / 1.8kg						
Test cycles		Helix/Bowie Dick/Vacuum test						

C€ C€ 0051 0497

Series: Type:	Lina 17 Lina PR013-003-17	Lina 22 Lina PRO13-003-22				
Chamber size:	17 I	22				
Power supply:	240 Vac Hz; 10 A					
Power consumption	er consumption 2 kW					
Dimensions overall (W x H x D):	450 x 435 x 599 mm					
Weight:	39 kg	40 kg				
Main/Used water tanks:	4 / 3.5 litres					
Working range:	5 to 10 cycles					
Usable space in chamber (W x H x D):	195 x 195 x 297 mm	195 x 195 x 390 mm				
Connection type:	1 serial port, 1 USB + 1 serial (optional), integrated automatic water filling valve (optional)					

Lina sterilizers were designed, certified and validated with the most stringent Directives and Standards:

93/42/EEC	Medical Device Directive			
2014/68/EU	Pressure Equipment Directive			
EN 13060	Small steam sterilizer			
IEC 61326-1	Electromagnetic compatibility			
IEC 61010-1	Safety requirements			
IEC 61010-2-040	Specific requirements for steam sterilizer			
The sterilizer can be validated according to EN ISO 17665-1				

Via Bolgara, 2 24060 Brusaporto (BG), Italy t +39 035-66 63 000 **f** +39 035-50 96 988 office.sterilization@wh.com